

SubConn® Low Profile

9 contacts


Connector specifications

Voltage rating	600 V DC/AC rms
Current rating	10 A per contact (max 40 A per connector)
Insulation resistance	> 200 MΩ
Contact resistance	< 0.01 Ω
Wet matings	> 500
Temperature rating (water)	- 4 to 60°C, 25 to 140°F
Temperature rating (air)	- 40 to 60°C, - 40 to 140°F
Storage temperature rating	- 40 to 60°C, - 40 to 140°F
Qualified pressure tested	1,400 bar, 20,300 psi (mated) 800 bar, 11,600 psi (open face)
Depth rating PEEK	300 bar, 4,350 psi

Material specifications


Connector body	Chloroprene rubber
Bulkhead body	Brass, stainless steel, titanium, anodised aluminium or PEEK
Contacts	Gold plated brass UNS - C36000
O-rings	Nitrile
Locking strap	Chloroprene rubber
Inline cable (2 ft, 60 cm or 16 ft, 5 m)	16 AWG, 1.31 mm ² synthetic rubber
Bulkhead leads (1 ft, 30 cm)	18 AWG, 0.82 mm ² coloured ETFE
OM leads (3", 7 cm)	18 AWG, 0.82 mm ² coloured ETFE

Face view (male)




Inline cable colour code



1 Black	4 Green	7 White/black
2 White	5 Orange	8 Red/black
3 Red	6 Blue	9 Green/black




LPIL9F





LPIL9M



LPBH9F





LPBH9M




LPOM9F





LPOM9M




LPDC9F



LPDC9M



LPB Strap



Drawing information

Dimensions in mm (1 mm = 0.03937 inches)
Threads in inches (1 inch = 25.4 mm)